

Рецептуры на платформе присадок Infineum для спецификаций моторных масел для пассажирских автомобилей в ЕС

Viscosity Grade		5W-30	5W-30	5W-40	5W-30	5W-40
Formulation (wt%)						
Infineum P6000	DI	12.00	12.00	12.00	12.00	12.00
Infineum SV261	VM	6.30	-	8.90	-	-
Infineum SV261L	VM	-	-	-	-	8.90
Infineum SV201	VM	-	6.60	-	-	-
Infineum SV203	VM	-	-	-	6.60	-
Infineum V385	PPD	0.30	0.30	0.30	0.30	0.30
ETRO 4	Group III	47.40	44.80	42.40	44.80	42.40
ETRO 6	Group III	34.00	36.30	36.40	36.30	36.40
Oil Properties						
KV 100°C, cSt		11.29	12.07	14.00	11.89	13.80
CCS @ -30°C, cP		4,522	4,975	5,320	4,810	4,910
HTHS, cP		2.9	3.5	3.5	3.5	3.5
Target Performance Claims						
API		SM/CF	SM/CF	SM/CF	SM/CF	SM/CF
ACEA		A5/B5, C2	A3/B4, C3	A3/B4, C3	A3/B4, C3	A3/B4, C3
OEMs			MB p229.31	MB p229.31	MB p229.51	MB p229.51
			VW502 00	VW502 00 / 505	VW502 00 /	VW502 00
			/505 00	00	505 00	/505 00
			BMW LL-04	VW505 01	BMW LL-04	VW505 01
				BMW LL-04		BMW LL-04
				Porsche		Porsche
*in progress						